

HENAN SICHENG ABRASIVES TECH CO.,LTD

Http://hngangyu.com

Add: Room 1903,Yaxing Time Squire,Songshan Road,Erqi District,Zhengzhou

City,Henan Province,China

Tel:+86-371-60900389 Fax:+86-371-60305637

Email: panchenhtml@gmail.com Emergency Telephone Number +86-13526538098



SICHENG ABRASIVES

BROWN FUSED ALUMINA F16 TECHNICAL DATA SHEET 棕刚玉 F16 技术参数表

PRODUCT/产品: Brown Fused Alumina F16/棕刚玉 F16

CHEMICAL COMPOSITION/化学成分:

Item	Guarantee Value/保证值 (%)	Typical Value/典型值 (%)
Al ₂ O ₃	≥95	95.28
Fe ₂ O ₃	≤0.3	0.14
SiO ₂	≤1.5	0.90
TiO ₂	≤3.0	2.85
CaO	≤0.45	0.30
Magnetic Content	≤0.05	0.041

PHYSICAL PROPERTIES/物理指标:

Specific Weight/比重	Hardness/硬度	Bulk Density/堆积密度	Melting Point/熔点
3.95 g/cm ³	9.0Mohs scale	1.82-1.91g/cm ³	2050°C

PARTICLE SIZE DISTRIBUTION/粒度分布:

Grit 粒度	Mesh#	Mesh size(um)	Weight Standard(%)	Typical Value(%)
Coarsest Grit 最粗粒	+10	2000	0	0
Coarse Grit 粗粒	+14	1400	Max. 20	8.6
Basic Grit 基本粒	+16	1180	Min. 45	43.6
Mixed Grit 混合粒	+16 +18	1180 1000	Min. 70	85.3
Fine Grit 细粒	-20	850	Max. 3	1.6

APPLICATIONS/应用场景:

- Bonded Abrasives/ 固结磨具
- Wear Resistance Floor/ 耐磨地坪
- Alumina Ceramics/ 氧化铝陶瓷
- Refractory/ 耐火材料